

| Component list | |
|----------------|-------------------------|
| Ref. | Item |
| 1 | 1 "C" Post |
| 2 | Threaded rods M20x250 |
| 3 | Blockout |
| 4 | Bolts TT M16x30 |
| 5 | Galvanized tube |
| 6 | Top Rail Splice plate |
| 7 | Bolts TE M12x70 |
| 8 | Corrugated Splice Plate |
| 9 | Top Rail |
| 10 | Bolts TTQST M10x100 |
| 11 | Protection Rail |
| 12 | Bolts TTQST M16x125 |
| 13 | Left Post Cover |
| 14 | Right Post Cover |
| 15 | Bolts TE M10x150 |


Measurements expressed in mm

Tightening torque:

Ref. 4 & 12 torque between 120 & 130 Nm

Torque values must be checked with a calibrated torque wrench

The bolts Ref. 12 are preassembled, remove the nuts to proceed with the installation



MARGARITELLI
ROAD SAFETY

| | |
|----------------------|----------------------|
| Drawing IM 020-01 | Issued 03/01/2005 |
| Review 05 | Date 20/06/2022 |

Object: Bridge Safety Barrier H2BP-01
Certificate of Costancy of Performance CE n° 0497/CPR/3153
Assembly instructions